



CONSTRUCTION	Tufting 1/10" loop pile
STRUCTURE	Tufté 1/10" bouclé
STRUKTUR	Getuftet 1/10" Schlinge
STRUCTUUR	Getuft 1/10" lussenpool
PILE MATERIAL	100% PA 6 IMPREL®
COMPOSITION DU VELOURS	
POLMATERIAL	
POOLMATERIAAL	
PRIMARY BACKING	Woven PP
SUPPORT	PP tissé
TRÄGERMATERIAL	PP Bändchengewebe
TUFTDOEK	Geweven PP
SECONDARY BACKING	Action Back
DOSSIER	
RÜCKEN	
TAPIJTRUG	
PILE WEIGHT	Ca.540 gr/m²
POIDS DU VELOURS	
POLEINSATZGEWICHT	
POOLGEWICHT	
TOTAL WEIGHT	Ca. 1.540 gr/m²
POIDS TOTAL	
GESAMTGEWICHT	
TOTAAL GEWICHT	
PILE HEIGHT	Ca. 3 mm
EPAISSEUR DU VELOURS	
POLHÖHE	
POOLHOOGTE	
TOTAL HEIGHT	Ca. 5 mm
EPAISSEUR TOTALE	
GESAMTHÖHE	
TOTALE DIKTE	
TUFT DENSITY	Ca. 220 000/m²
NOMBRES DE POINTS	
NOPPENZAHL	
AANTAL PUNTEN	
PILE DENSITY	Ca. 0.110 g/cm³
DENSITÉ DU VELOURS	
POLROHDICHTÉ	
POOLDICHTHEID	
CLASSIFICATION	EN 1307
CLASSEMENT	32 - LC1
KLASSIFIKATION	
CLASSIFICATIE	
UPEC	U3 P3 E1 C0
	Certification CSTB:10/278
CASTOR CHAIR SUITABILITY	EN 985
CHAISE À ROULETTES	A: intensive use
STUHLROLLENEIGNUNG	
ROLSTOELGESCHIKTHEID	
STAIR SUITABILITY	EN 1963
ESCALIERS	A: intensive use
TREPPENEIGNUNG	
TRAPPENGESCHIKTHEID	



PERMANENTLY ANTISTATIC	ISO 6356
ANTISTATIQUE PERMANENT	< 2 kV
PERMANENT ANTISTATISCH	
PERMANENT ANTISTATISCH	
IMPACT NOISE RATING	ISO 140-8
ISOLATION PHONIQUE	ca. 22 dB ΔLw
TRITTSCHALLVERBESSERUNG	
GELUIDSISOLATIE	
SOUND ABSORPTION	ISO 354
ABSORPTION PHONIQUE	ca. 0.20 αw
SCHALLABSORPTIONSGRAD	
GELUIDSABSORPTIE	
THERMAL RESISTANCE	ISO 8302
RÉSISTANCE THERMIQUE	0.11 m² K/W
WÄRMEDURCHLASSWIDERSTAND	
WARMTEDOORLAATWEERSTAND	
FASTNESS TO LIGHT	ISO 105-B02
SOLIDITÉ À LA LUMIÈRE	≥ 5-6
LICHTECHTHEIT	
LICHTECHTHEID	
COLOUR FASTNESS TO WATER	EN ISO 105-E01
SOLIDITÉ À L'EAU	≥ 4-5
WASSERECHEITHEIT	
WATERECHEITHEID	
FIRE RESISTANCE	EN 13501-1
COMPOTEMENT AU FEU	Cfl-s1 (if glued)
BRENNVERHALTEN	
BRANDGEDRAG	
RUBBING FASTNESS	EN ISO 105-X12
SOLIDITÉ AU FROTTEMENT	≥ 4
REIBECHTHEIT	
WRIJFECHTHEID	
NUMBER OF COLOURS	12
NOMBRES DE COULEURS	
ANZAHL FARBEN	
AANTAL KLEUREN	
WIDTH	EN ISO 3018
LARGEUR	ca. 400 cm (12 colours)
BREITE	ca. 500 cm (10 colours)
BREEDTE	





▲ ProQI3700 4 m

▲ ProQI3900 4 m








▲ ProQI4300 4&5 m

▲ ProQI4800 4&5 m

▲ ProQI1200 4&5 m

▲ ProQI9300 4&5 m

▲ ProQI9500 4&5 m



▲ ProQI7500 4&5 m

▲ ProQI7800 4&5 m

▲ ProQI9800 4&5 m

▲ ProQI9600 4&5 m

▲ ProQI9900 4&5 m