




CONSTRUCTION	Tufting 5/64" twist pile	PERMANENTLY ANTISTATIC	ISO 6356
STRUCTURE	Tufté 5/64" frisé	ANTISTATIQUE PERMANENT	≤ 2 kV
STRUKTUR	Getuftet 5/64" Frisé	PERMANENT ANTISTATISCH	
STRUCTUUR	Getuft 5/64" frisé	PERMANENT ANTISTATISCH	
PILE MATERIAL	100% PA 6 IMPREL®	IMPACT NOISE RATING	ISO 140-8
COMPOSITION DU VELOURS		ISOLATION PHONIQUE	26 dB ΔLw
POLMATERIAL		TRITTSCHALLVERBESSERUNG	
POOLMATERIAAL		GELUIDSISOLATIE	
PRIMARY BACKING	Woven PP	SOUND ABSORPTION	ISO 354
SUPPORT	PP tissé	ABSORPTION PHONIQUE	0.20 αw
TRÄGERMATERIAL	PP-Bändchen	SCHALLABSORPTIONSGRAD	
TUFTDOEK	Geweven PP	GELUIDSABSORPTIE	
SECONDARY BACKING	Action Back	THERMAL RESISTANCE	ISO 8302
DOSSIER		RÉSISTANCE THERMIQUE	0.12 m² K/W
RÜCKEN		WÄRMEDURCHLASSWIDERSTAND	
TAPIJTRUG		WARMTEDOORLAATWEERSTAND	
PILE WEIGHT	Ca. 1.300 gr/m²	FASTNESS TO LIGHT	ISO 105-B02
POIDS DU VELOURS		SOLIDITÉ A LA LUMIÈRE	≥ 5-6
POLEINSATZGEWICHT		LICHTECHTHEIT	
POOLGEWICHT		LICHTECHTHEID	
TOTAL WEIGHT	Ca. 2.126 gr/m²	COLOUR FASTNESS TO WATER	EN ISO 105-E01
POIDS TOTAL		SOLIDITÉ À L'EAU	≥ 4-5
GESAMTGEWICHT		WASSERECHEIT	
TOTAAL GEWICHT		WATERECHEID	
PILE HEIGHT	Ca. 6,5 mm	FIRE RESISTANCE	EN 13501-1
EPAISSEUR DU VELOURS		COMPORTEMENT AU FEU	Cfl-s1
POLHÖHE		BRENNVERHALTEN	only with full adhesion
POOLHOOGTE		BRANDGEDRAG	
TOTAL HEIGHT	Ca. 8,6 mm	RUBBING FASTNESS	EN ISO 105-X12
EPAISSEUR TOTAL		SOLIDITÉ AU FROTTEMENT	≥ 4
GESAMTHÖHE		REIBECHTHEIT	
TOTALE DIKTE		WRIJFECHTHEID	
TUFT DENSITY	Ca. 274 400/m²	NUMBER OF COLOURS	24
NOMBRES DE POINTS		NOMBRES DE COULEURS	
NOPPENZAHL		ANZAHL FARBEN	
AANTAL PUNTEN		AANTAL KLEUREN	
PILE DENSITY	Ca. 0.159 g/cm³	WIDTH	EN ISO 3018
DENSITÉ DU VELOURS		LARGEUR	ca. 400 cm
POLROHDICHTE		BREITE	
POOLDICHTHEID		BREEDTE	
CLASSIFICATION	EN 1307		
CLASSEMENT	33 - LC5		
KLASSIFIKATION			
CLASSIFICATIE			
CASTOR CHAIR SUITABILITY	EN 985		
CHAISE À ROULETTES	A: intensive use		
STUHLROLLENEIGNUNG			
ROLSTOELGESCHIKTHEID			
STAIR SUITABILITY	EN 1963		
ESCALIERS	A: intensive use		
TREPPENEIGNUNG			
TRAPPENGESCHIKTHEID			






▲ ProDA3 600 ▲



▲ ProDA3 500 ▲



▲ ProDA3 400 ▲




▲ ProDA9 000



▲ ProDA3 900



▲ ProDA4 300



▲ ProDA7 800



▲ ProDA7 400



▲ ProDA9 500




▲ ProDA9 300



▲ ProDA4 900



▲ ProDA4 700



▲ ProDA7 200



▲ ProDA5 300



▲ ProDA5 400



▲ ProDA9 600



▲ ProDA9 700




▲ ProDA4 800




▲ ProDA2 700



▲ ProDA2 300



▲ ProDA1 000



▲ ProDA1 700



▲ ProDA9 800



▲ ProDA9 100